-CARE

MAINTENANCE
PRODUCTS FOR
YOUR WOODEN
FLOOR CARE

**THANK
YOU FOR
CHOOSING
A BRUNO
WOODEN FLOOR**



More and more people choose wooden floor for interior design because of its many qualities as natural material plenty of aesthetic values and many functional advantages.

Because of old soft wax finishing, with low resistance to use and dirt and which needed frequent restoration, you may have some doubts about wooden floor maintenance. But now, modern varnished oil effect or oil U.V. finishing wooden floors do not need any particular or more demanding care than other hard material flooring such as ceramics, stones, terracotta tiles, etc.

Anyway, even if some small attention and our specific care products are enough to right maintain your parquetry, wooden floor care should not be ignored.

For this reason, following parquet floor production step by step from the beginning, we have developed a specific care product line. This leaflet aims to give you some useful advice to keep your beautiful wooden floor always in order.

ROUTINE MAINTENANCE FOR: VARNISHED OIL EFFECT AND OIL U.V. WOODEN FLOOR

B-WASH / B-BRIGHT

In order to maintain your parquet floor in good condition, we suggest you to put a doormat on the threshold.

The main problems with wooden floors are actually caused by dust and abrasive particles under your shoes. Apart from dust removal (with vacuum systems or specific dust clothes), the wooden surface has to be carefully washed and cleaned from time to time. On this purpose, our **B-WASH**, a neutral soap which does not leave surface-active residuals when the floor dries off and does not make the surface opaque, is highly suggested. This product should be diluted with water and the rag should be well squeezed, so not to "wash" the floor, but to clean it with a humid cloth. If your varnished oil effect or oil U.V. wooden floor presents some opacities or small abrasions, you can refurbish its original shine with our **B-BRIGHT**, a lavender oil wax which not only nourishes the floor but also leaves a pleasant scent. The wax should be spread with a soft woollen cloth or with a polisher with soft felt pads.

ROUTINE MAINTENANCE FOR: OILED WOODEN FLOOR

NACASA / NAPLANA

In case of oiled wooden floor, **NACASA**, an ecological soap which gently wash the surface, and **NAPLANA**, a protective natural wax, are highly recommended.

EXTRAORDINARY MAINTENANCE FOR: VARNISHED OIL EFFECT AND OIL U.V. WOODEN FLOOR

B-WASH / B-MATT

In case of worn out or ruined wooden floor, we suggest you to clean the surface with **B-WASH** and use then the metallized wax **B-MATT**.

If the floor is really very ruined, apply B-MATT once again.

MAINTENANCE FOR: OUTDOOR WOODEN PLANKS

DECK-SOAP / DECK-OIL

Bruno wooden planks for outdoor are made of hard and weather resistant wooden species. Obviously, since exposure to atmospheric agent causes wood chromatic decay (surface greying), periodic maintenance with our Deck Soap and Deck Oil is highly recommended.

DECK SOAP is a nourishing cleaning soap suitable for outdoor wooden floor washing, which efficiently remove dirt, saltiness, chlorine residual, etc. **DECK OIL** is highly recommended in order to brighten the wood aspect.

This is a preservative oil composed of special anti-decay agents which, if regularly used, maintains the wood colour intact.

B-WASH

Features: natural detergent for varnished oil effect and oil U.V. wooden floor cleaning. It acts to remove even the most persisting stains, wheel marks and other stains without leaving any glows, and also leaves a pleasant hygienical perfume.

How to use: apply B-Wash using a soft cloth on persisting stains. If necessary, apply more specifically using a cotton sponge. In all other cases dilute the product with water in the proportion of 1 measure of B-Wash and 10 measures of water. It does not leave any glows and leaves a delightful fresh perfume.



B-BRIGHT

Features: his water emulsion of industrial waxes has been especially created for the care of oil effect and oil U.V. wooden floors. This wax gives the floor a high degree of non-slip protection and a good degree of anti-static properties.

How to use: dilute with water to a proportion of 1:4 and apply the solution uniformly. Wait for B-Bright to dry and then polish using a soft woollen cloth or polishing machine with soft felt section.



B-MATT


Features: it is a pre-metallized wax for the maintenance of ruined and/or abraded oil effect and oil U.V. floors.

Because of its polymeric structure, it gives the treated surface a glossy and even aspect.

How to use: clean very well the floor and spread B-Matt uniformly. For particularly heavily used floors apply a second coat of B-Matt when the first coat has completely dried.




NACASA

Features: eco-friendly every-day soap, suitable for  products. It softly clann your floor and pleasantly fills the room.

How to use: dilute 1 measuring cap of NACASA each 5 litre water.



NAPLANA

Features: eco-friendly wax emulsion from natural raw material, suitable for  products maintenance.

It protects and treats the surface.

How to use: dilute 1-4 measuring caps of NAPLANA each 5 litre water.



DECK-SOAP

Features: a nourishing detergent to clean external wooden floors. It efficiently removes dirt, traces of chlorine, salt, etc...

How to use: shake well before use. Dilute the product with water to a ratio of 1 of Deck-Soap + 4/5 of water. Wash a first time using floor cloth or mop. When dry, wash a second time with the clean product. The floor can be walked on immediately. It does not leave glows.



DECK-OIL

Features: it's an impregnator particularly recommended for the treatment of external wooden floors (swimming pool edges, verandas, walkways). It contains natural and synthetic oils, with the addition of UV ray absorbers and special anti-ageing ingredients against the deterioration of wood. It also protects wood against attack from wood-eating insects.

How to use: before applying Deck-Oil, prepare the wood; sanding with 60/80 sandpaper is recommended in order to obtain a slip-proof effect when the floor is wet. Apply the first coat of Deck-Oil, and after 24/48 hours apply a second coat, without sanding.





Bruno Srl - Corso Francia, 7G - 12084 Mondovì (CN)
Tel. +39 0174 562727 - Fax +39 0174 562728
www.brunoparquet.it - info@brunoparquet.it