


LOBACURE



LOBADUR



LOBASOL



LOBACARE



LOBATOOL



Products 2016/17

The LOBA History
Tradition and Innovation

► 1922 Founding

On 13 April 1922 Wilhelm Hornung and Dr Max Fischer establish „Vereinigte Wachswarenfabriken AG Hornung und Dr Fischer“ in Ditzingen, near Stuttgart. Its products include floor stains, ski wax and household candles.

► 1952 Expansion

The company expands its product range, developing and manufacturing paints and varnishes.

► 1959 Pioneering work

LOBA launches the world’s first commercially available thermal insulation composite system, under the brand name Dryvit®, making a major contribution to energy saving.

► 1995 Leadership

With its two-component, waterborne finishing systems, LOBA sets new standards that remain unmatched to this day.

► 2012 Innovation

LOBA launches LOBACURE, the latest generation of finishing systems with on-site UV curing – setting new standards in floor refurbishing.

► 2015 Investment

LOBA builds a new logistics and training centre.



► Competence on a global scale

With partners in more than 60 countries, LOBA is a competent partner for the finishing and maintenance of wood and cork floors.

Web



- News
 - Updates
 - Important information
- www.loba-usa.com



- Safety Data Sheet
 - Technical information
 - Application videos
 - Etc.
- www.loba.de/us/downloads.html



Reachable also from your mobile devices



www.loba-usa.com



Content

LOBACURE	7	UV on-site Waterborne Finish
LOBADUR	9/10	Waterborne Finishes
	10	Stain
	11	Sealers
	12	Additives
	12	Dust-free Recoating
LOBASOL	14	Natural Oil
	14	Pre Treatments
LOBACARE	16-18	Care & Maintenance products
LOBATOOL	20/21	Tools & Accessories

LOBA Know-how	2	LOBA History
	4	Environmental Responsibility
	5	LOBA Philosophy
	22	Suitability list for Sealers
	23	Suitability list for HS 2K ImpactOil

Pictograms

C Cork	Contents	Brush application	Wipe
W Wood	Packing	Roller application	Apply coat
P PVC	Pallet	Trowel	Thorough cleaning
L Linoleum	Drying time	T-bar	Apply with cloth
Connected Systems: Guarantee for systems of LOBADUR® waterborne finishes and Wakol adhesives	sq ft/gallon Consumption in gallon	Care applicator	Trim-Pad



Enviromental Responsibility

For us, environmental responsibility means: taking action

Out of a sense of responsibility for our customers, our employees and our environment we have been committed to the development of waterborne and low-emission products for many years now. We reduce solvent content and use natural raw materials. Furthermore, the VOC content of our waterborne finishes is far below California's SCAQMD Rule 1113 which sets the limit to 275 g/L VOC.

LOBA's quality and environmental management system is in accordance with ISO 9001:2008 and 14001:2004 certified.

Quality seals and ecolabels, as well as their test criteria

The main criteria for the award of an ecolabel are the limitation of the above-described **SOLVENT CONTENT** and the closely associated **EMISSIONS TEST**, which assesses the quality of indoor air. Often an **ASSESSMENT OF THE PRODUCT'S COMPOSITION** is also performed in order to check whether it contains substances hazardous to human health and the environment.

	Ü	EC1	GREEN MARK	CEC	GREEN MARK	GREEN MARK
Test of solvent content	✓	✓	✓	✓	✓	✓
Emissions test	✓	✓		✓	✓	✓
Composition assessment	✓		✓			

The Ü mark (German Mark of Conformity) is required in Germany. When it comes to health and environmental protection, you can play it safe by choosing products labelled with this mark in combination with the EMICODE®.

* (VOC = Volatile Organic Compound)

Certified LOBA products



LOBACURE

WS Rush A.T.	✓	✓	✓	✓
--------------	---	---	---	---

LOBADUR

2K InvisibleProtect A.T.	✓			
2K Supra A.T.	✓			
WS 2K Supra (USA)			✓	✓
Hybrid A.T.	✓		✓	
WS EasyFinish	✓	✓	✓	✓
WS EasyPrime	✓	✓	✓	✓
OptiFinish	✓		✓	✓
HS 2K Intensive A.T.	✓			

LOBASOL

HS 2K ImpactOil	✓		✓	✓	✓
HS 2K ImpactOil Color	✓		✓	✓	✓



The LOBA Philosophy



This is **Max!**

We would like to introduce **Max: a real professional, like you and like the surface specialists at LOBA.**

Max symbolises our close connection to the contractors and our understanding of everything you need as a wood flooring professional. **So whenever you encounter Max, you'll know: you can count on top quality from LOBA.**

LOBA. On Top ! Quality and reliability the basis for your success.

The wood and cork floor specialist Max recommends finishing and floorcare systems from LOBA: no compromises.

What you can expect from LOBA:

Maximum reliability and the latest technology for your everyday work. After all, for perfect results you need the specialist. You are a specialist in your field, and so are we: LOBA is the only German, medium-sized company specialising exclusively in the surface treatment of wood and cork flooring. This makes LOBA a leading manufacturer of finishing and floorcare systems.

Our specialist philosophy: LOBA. On Top !

- "On Top !" stands for our specialisation in floor-finish systems: finishing, oiling/waxing, cleaning and maintenance.
- "On Top !" stands for our position as a leader in research and development. For top quality and reliability in product application.
- "On Top !" stands for added value through customer service: consultation, training and practical assistance with product application.

As a leading manufacturer and internationally recognised specialist, LOBA offers the highest level of experience. You can profit directly from this expertise. Our position as a leader in research and development is the basis for maximum quality and reliability in product application. Our collaborative approach is demonstrated by our commitment to providing reliable customer service, competent training and active support for all your questions.

LOBA – the surface specialist for wood and cork floors




UV on-site Waterborne Finishing systems – Floors done at the speed of light!

The new generation of finishing systems.

LOBA opens up new opportunities for you. The innovative and high-quality LOBACURE UV finish for wood floors puts an end to time consuming curing and expensive downtimes for your customers. A solid argument which underscores your efficiency. Reaches full hardness and usability instantly with UV curing.

LOBA. On Top! Quality and reliability as the basis for your success.





WS Rush

• Waterborne UV-finish
• Excellent scratch resistance and durability
• Exceptional chemical resistance
• Extremely low VOC (VOC <10g/L)
• Easy application

Item No. sheen
LO-FI-117 semi-gloss
LO-FI-129 satin


2,5 U.S. gallon 1 60

VOC 7 g/L

h 2-3

sq ft/gallon 500-700

Buff and recoat with WS Rush – refinishing floors without downtime.



* Allow to dry in accordance with Technical Information.

Supported by:




Federal Ministry of Economics and Technology




ZIM
für wachstum
Zentrales Innovationsprogramm
Mittelstand

on the basis of a decision by the German Bundestag



The ideal tool for UV-curing.

The curing process requires UV floor-curing equipment in compliance with technical specifications. Based on practical experience, LOBA recommends the DecoRad® Floormate. This machine is powerful and easy to use, and its clever design guarantees perfect results every time.



Waterborne Finishing Systems – Naturally strong!

LOBADUR® – always the right product

The waterborne finishing systems of the LOBADUR® WS product line offers an impressively broad range of applications: They can be used for floors with moderate to high traffic, for a matt or high-gloss finish and for stained floors. LOBA primers do not leave lap marks, offering an ideal quality of application. They also minimise side bonding.



NEW

C

W











Item No. LO-FI-238

2K InvisibleProtect
Two-component waterborne thin film coating with outstanding chemical resistance, scratch resistance and wear resistance for wood and cork floors.

- Looks and feels like natural untreated wood
- Very easy to apply
- Self sealing – no primer needed
- Excellent chemical resistance
- Non ambering, keeps the natural appearance of the wood
- Create the look of natural oil with the prior use of HS 2K Intensive ^{A.T.}

		
1 U.S. gallon	4	144

VOC	130 g/L
 	
	4-6
sq ft/gallon	400-500



C

W

L

P











Item No. sheen
LO-FI-100 gloss
LO-FI-159 semi-gloss
LO-FI-157 satin

2K Supra
Based on state-of-the-art ceramic technology, this waterborne, two-component pure polyurethane finish sets new standards in wood floor finishing for very high traffic commercial areas.

- Ready for full use after 24 hours!
- Exceptionally high scratch resistance
- Extremely high elasticity
- Excellent chemical and wear resistance
- Non yellowing

		
1 U.S. gallon	4	144

VOC	150 g/L
 	
	2-3
sq ft/gallon	500-600



C

W











Item No. sheen
LO-FI-049 semi-gloss
LO-FI-048 satin
LO-FI-047 extra-matte

WS 2K Supra
Two-Component Commercial Finish

- Waterborne Polyurethane formula with extreme wear resistance
- Easy to mix, no equipment needed
- Excellent build through high solid content
- No bubbling, perfect leveling and flow
- Easy to use, can be applied by T-Bar, lambswool, brush or roller
- Non yellowing
- Water clean-up
- Perfect for cork floors
- VOC compliant
- No lap marks or streaks
- Fast drying

		
1 U.S. gallon	4	144

VOC	semi-gloss, satin 125 g/L
	extra matte 70 g/L
 	
	2-3
sq ft/gallon	500-600



W











Item No. sheen
LO-FI-057 semi-gloss
LO-FI-067 satin

Hybrid
High performance, one-component, waterborne oil fortified polyurethane finish for wood floors with exceptional scratch resistance.


- Outstanding scratch resistance
- Astonishing color
- Superior leveling
- Excellent build through high solid content
- Application without primer
- No side bonding
- Approved as 2 coat system on red oak for residential use
- Dries in 2 hours
- Cures 80% in 24 hours

		
1 U.S. gallon	4	200

VOC	188 g/L
 	
	4-6
sq ft/gallon	500-600



CW





WS EasyFinish

One-Component Finish for high traffic areas

- Waterborne Polyurethane formula with excellent wear resistance
- No pot life, no waste, no crosslinker necessary
- Excellent build through high solid content
- No foaming, perfect leveling and flow

- Easy to use, can be applied by T-Bar, applicator, brush, lambswool or roller
- Non yellowing
- No lap marks or streaks
- Fast drying

VOC	205 g/L
	
	2-3
sq ft/gallon	500-600

Item No. sheen

LO-FI-011 gloss


LO-FI-014 semi-gloss

LO-FI-012 satin


1 U.S. gallon

4

200



W





OptiFinish

One-Component polyurethane acrylate waterborne finish for high end residential wood floors.

- No lap marks
- Exceptional build
- Self-sealing

- Economical yet very good durability
- Low VOC
- Non yellowing

VOC	semi-gloss 181 g/L
	satin 215 g/L
	
	2-3
sq ft/gallon	500-600

Item No. sheen

LO-FI-163 semi-gloss

LO-FI-162 satin

1 U.S. gallon

4

200

Stain



W



Stain

Stain for the professional coloring of wood floors

- Reduces the side bonding tendency of waterborne finishes
- Easy application, absolutely lapmark free!
- Can be coated with any LOBADUR® waterborne finish
- Available in a variety of colors

- No bleed back
- Soft grain of the wood does not become dark
- Very high coverage
- 1 hour dry time

VOC	800 g/L
	
	2
sq ft/quart	200-250

1 U.S. quart

12

LO-FI-036

Ebony

LO-FI-037

Golden Brown

LO-FI-039

Mesquite Red

LO-FI-040

Neutral

LO-FI-041

Provincial

LO-FI-044

Spice Brown

LO-FI-043

Sedona Red

LO-FI-035

Billinga

LO-FI-038

Jacobean

LO-FI-042

Royal Mahogany

LO-FI-046

Walnut

LO-FI-045

Strong white

LO-FI-034

Amber

LO-FI-198

Golden Oak

LO-FI-199

Antique Brown

LO-FI-200

Classic Grey


LO-FI-201

Weathered Oak


LO-FI-202

Gunstock

These are only color examples. Please make your own color samples on the wood you use.



W





WS EasyPrime

Waterborne sealer for wood floors

- Reduce side-bonding
- Can be finished with all LOBADUR® waterborne finishes
- No foaming, perfect leveling and flow
- Easy to use, can be applied by T-Bar, lambswool, applicator, brush or roller

- Excellent coverage rate
- Non yellowing, protects the natural color of the wood
- No lap marks or streaks
- Fast drying
- Suitable for almost all wood species

VOC	171 g/L
	
	1-2
sq ft/gallon	400-500


Item No. sheen

LO-FI-015 transparent


1 U.S. gallon

4

200



W





HS 2K Intensive/Color

High-solid sealer based on natural oils. Also available in 10 trendy colors.

- Easy to apply with a roller, leaving no lap marks
- Natural looking warmth and color
- No grain rise
- Can be overcoated with any LOBADUR® waterborne finish

- Combination of an oiled look with the advantages of a sealed finish
- 93% solids
- Cobalt and methylethyl ketone oxime free

VOC	<70 g/L
	
	12
sq ft/gallon	540

Item No. sheen

LO-FI-239 transparent

LO-FI-239 color

2,5 kg/0,66 gallon

4

120

2,5 kg/0,66 gallon

4

120

LO-FI-239

Transparent

LO-FI-244

Mesquite Red

LO-FI-251

Jacobean

LO-FI-247

Golden Oak

LO-FI-249

Gunstock

LO-FI-252

Provincial

LO-FI-245

Spacial Walnut

LO-FI-253

Classic Grey

LO-FI-250

Ebony

LO-FI-246

Sedona Red

LO-FI-254

Country White

LO-FI-248


Weathered Oak

These are only color examples. Please make your own color samples on the wood you use.





- WS Argo**
Dry time retarder for Waterborne Finishes
- Waterborne additive to prolong the drying time of LOBADUR® waterborne finishes
 - Does not alter or effect the finish quality in any way
 - Easy to apply, safe to handle
 - Excellent coverage rate
 - Environmentally friendly and VOC compliant
 - No lap marks or streaks
 - Double the open time

Item No.		
LO-FI-003	6.5 fl.oz.	12





- WS UV-Protect**
- Easy to use
 - VOC compliant, safe to handle
 - Additive for all LOBADUR® waterborne finishes
 - Very effective protection against UV light
 - Does not alter finish appearance
 - Solvent-free
 - Protects light colored wood species from yellowing through sun light
 - One 100 ml bottle is added to one U.S. gallon
 - Easy to mix
 - Works with all LOBADUR® waterborne finishes

Item No.			VOC
LO-FI-052	100 ml / 3.38 fl.oz.	15	0 g/L solvent-free



- WS Amberizer**
- Adds the look of oil based finish
 - Great for touch ups and repairs of old floors
 - Convenient package and great color consistency: one amberizer per gal of finish
 - Suitable for all LOBADUR® waterborne finishes

Item No.			VOC
LO-FI-001	100 ml / 3.38 fl.oz.	15	14 g/L

Dust-free Recoating





C

W

- WS 2K Contact**
Waterborne adhesion promoter for the recoating of factory prefinished floors
- No sanding necessary, no special machines – no dust
 - VOC compliant – WS 2K Supra qualifies for LEED credits EQ 4.2
 - Great for coating of hand scraped and distressed floors
 - 4 simple steps, the C⁴ System

Item No.		
LO-FI-008	1 U.S. quart	4

VOC	250 g/L
	
	1-2
sq ft/quart	500-600

Floor Oils – nothing beats Natural Beauty.

Beautiful appearance, excellent properties

The attractive appearance of oiled finishes brings out the pleasantly warm naturalness of the wood. And no other products do this better than LOBA's modern and completely solvent-free oil and wax systems made from natural raw materials. Products from the LOBASOL® range are known and loved for their environmental compatibility and out-standing properties. With their high wear resistance, moisture- and dirt-repellent properties and exceptional chemical resistance LOBASOL® products are the ideal solution for the most demanding applications.





HS 2K ImpactOil/Color

Durable two component oil for wood floors. Based on 100% natural vegetable oils. For high traffic commercial areas.


- Two-component oil contains no solvents and features 100 % solid content
- Water-repellent
- High durability
- Fast drying
- Available in 18 colors
- Creates slipresistant surfaces

transparent	2.5 kg/ 0.66 gallon	4	120
colors	0.75 kg/ 25.4 fl. oz	4	400
sample	100ml/ 3.4 fl. oz	1	-

SampleKit with trial sizes of the reactive stains, pigment stain and all 19 colors of HS 2K ImpactOil Color.

SampleKit 19 x 0,1l + 2 x 0,1l ActiveColor + 1 x 0,1l PreTone

VOC	0	
	Transparent	Color
	12	12
sq ft/gallon	600-800	800-1300
sq ft/2.5 kg	400-500	-
sq ft/0,75 kg	-	150-250



These are only color examples. Please make your own color samples on the wood you use.

PreTreatments



ActiveColor

Waterborne, solvent-free reactive stain for achieving natural color effects. On raw tannic-acid containing types of wood such as oak. The color intensity depends on the tannic-acid content in the wood. The tannic-acid free sapwood parts do not react with stain. As a result unique natural color effects similar to smoked oak can be achieved. In combination with HS 2K ImpactOilColor many different further color effects can be achieved.

Item No.	Color			
LO-FI-154	brown	2.5 l	4	144
LO-FI-153	grey	2.5 l	4	144

	12-24
sq ft/l	110-130



NEW

PreTone

Waterborne coloring system to enhance, customize or intensify the color of LOBASOL® HS 2K ImpactOil Color or LOBADUR® HS 2K Intensive A.T. Available in three colors.

Item No.	Color			
LO-FI-237	white	2.5/0.1 l	6/15	144/-
LO-FI-241	brown	2.5/0.1 l	6/15	144/-
LO-FI-240	black	2.5/0.1 l	6/15	144/-

	12-24
sq ft/l	110-130



Floor-care and Cleaning Products – Reliable Protection is the Best Maintenance!



Protect and maintain

The professional care of cork and wood is a decisive factor in the protection and maintenance of these valuable floors after they have been finished. And what could be easier than profiting from LOBA's extensive competence in the development of care and maintenance products? After all, the long-term protection of floors is part of LOBA's philosophy! Our wide range of products means that you will find just the right solution for every application.

By recommending LOBACARE® you are offering your customers optimal floor care.



Remover
Low-foaming basic cleaning concentrate for heavily soiled floors and for removing old floor-care layers

- Strong cleaning ability
- Does not contain any oil or wax, or leave any residue on the surface
- Removes wax and grease from old floors before recoating

- Removes LOBACARE® FloorCare without hurting the finish coat
- pH neutral

Item No.
LO-MA-009

1 U.S. quart

12

660

min

30-60

sq ft/quart

500-1000



ParkettSoap R2U
Waterborne deep cleaning solution for all oiled floors

- Ready to use product no dilution necessary
- Removes oil, dirt, dust
- The floor has to be reoiled after cleaning with ParkettSoap R2U

- also suitable for cleaning outdoor furniture

Item No.
LO-MA-010

1 U.S. gallon

4

200

h

12

sq ft/quart

1000



Hardwood Floor Cleaner
Spray Cleaner for Hardwood Floors

- Easy to use
- Hygienic
- Dries without streaking
- Suitable for wood, cork, PVC, polyolefin, rubber, stone, laminate floors and ceramic tiles

- Excellent cleaner without dangerous chemicals
- Does not leave any residue
- Environmentally friendly

Item No.
LO-MA-005 Hardwood Floor Cleaner
LO-MA-018 Refill

1 U.S. quart
250 ml

12
12

660
-

min

15

sq ft/quart

5000



Floor Cleaner Concentrate
Cleaner concentrate for all hard surfaces

- Mix with water 1:100

Item No.
LO-MA-004

1 U.S. quart

12

660

min

30

sq ft/quart

500 000

Maintenance Cleaning

Care products



SprayMop Set
Practical mop with integrated spray system specially developed for the cleaning of wood and cork floors. As well as for all waterresistant surfaces.

Contents:

- SprayMop (2-part handle, SprayMop frame)
- Microfibre mop head
- Refillable reservoir for cleaning solution
- Refill 250 ml

- Fast and easy cleaning, no bucket required
- No more excess moisture on the floor

Item No.
LO-FI-019 SprayMop Set
LO-MA-020 Cover Replacement
LO-MA-018 Refill

1
1
250ml

-
-
-

-
-
-

min

30-60

sq ft/quart

250



FloorCare
Waterborne care product for finished wood floors and cork floors

- Provides a protective layer
- Can be removed without sanding
- Easy to apply

- VOC compliant
- No lap marks or streaks
- Excellent adhesion

Item No.
LO-MA-003 semi-gloss
LO-FI-002 satin

1 U.S. quart

12

660

min

30-60

sq ft/quart

250


**NatureOil**

Innovative, sustainable product with exceptional properties and the first of its kind on the market!

- Waterborne natural oil based on renewable raw materials
- Prolongs the water repellency of the original floor
- Reliably retains the natural sheen of the oiled floor
- Ready to use
- Solvent free



Item No.
LO-FI-115



4-6

sq ft/quart	350-1000
-------------	----------




ParkettOil

- Easy-to-apply maintenance oil made from natural raw materials
- Retains the matt finish of oiled floors
- No self-polishing
- Suitable as spot treatment
- Refreshes the floor's finish while removing lap marks and other dirt and grime
- Removes wear marks



Item No.
LO-MA-007



12


sq ft/quart	800-1000
-------------	----------

Care and maintenance system

	Wood floors		Factory-prefinished wood floors		Cork
	finished	oiled	finished	oiled	finished
Initial Care					
normal	FloorCare	–	FloorCare	–	FloorCare
Maintenance					
Cleaning	Hardwood FloorCleaner	Hardwood FloorCleaner	Hardwood FloorCleaner	Hardwood FloorCleaner	Hardwood FloorCleaner
Care	FloorCare	Oilcare: ParkettOil NatureOil	FloorCare	Oilcare: ParkettOil NatureOil	FloorCare
Deep cleaning					
	Remover	ParkettSoap R2U	Remover	ParkettSoap R2U	Remover

Please look up our Technical Information for information about dilution and consumption for each product.
Receptable in the internet: www.loba-usa.com

Tools and Accessories – the Choice of Professionals!



Success is not an accident

For quality results you need not only the right finishing system, but also the right tools. This is why LOBA extensively tests every applicator and every tool before it is added to the LOBATOOL product line. These high quality standards guarantee the trouble-free use of our products. Numerous professionals have learned to trust LOBA's recommendations and rely on LOBATOOL. Play it safe with LOBA!



Roller 'Micro 60-80'
Roller to apply LOBASOL® HS 2K ImpactOil transparent, LOBADUR® HS 2K Intensive ^{A.T.}.

Item No.
LO-FI-032



12



Roller 'Micro 120'
Roller to apply all LOBADUR® waterborne finishes.

Item No.
LO-FI-031



12



Roller 'Universal 100'
Roller to apply LOBACURE WS Rush ^{A.T.}.

Item No.
LO-FI-126



12



Edge Roller
Small roller for edges. Make sure to order the special roller handle for edge rollers.

Item No.
LO-FI-116



12



Roller Handle
LO-FI-077: 25cm for Roller Micro 60-80, Micro 120 and Universal 100
LO-FI-017: 10cm for Edge Roller



1



Roller Pole
Telescope-extension, adjustable up to 8 feet

Item No.
LO-FI-127



1



Roller Tube
To protect the roller

Item No.
LO-FI-033



1



Bucket
Varnish bucket with lid and measuring scale. PE liners for the varnish bucket.

Item No.
LO-FI-005 Bucket
LO-FI-029 Inlays/liner bag



1

25



Trowel
Flat trowel to apply LOBADUR® WS 2K Contact, LOBASOL® HS 2K ImpactOilColor

Item No.
LO-FI-059 27cm/ 11inch
LO-FI-051 35cm/ 13inch



6



Care applicator Wischwiesel
Applicator for LOBACARE® FloorCare

Item No.
LO-FI-055



1



Special-Pad ø 406 x 10mm, ø 16 inches
Brown: Buffing pad for LOBASOL® products
Green: Buffing pad for deep cleaning with LOBACARE® Remover

Item No.
LO-FI-004 brown
LO-FI-020 green



10



Hand-PadSet
Ideal for staining and oiling border areas
1 pad holder, 25 pads beige

Item No.
LO-FI-022



1



PerforatedPad/ DustPad ø 16 inches
PerforatedPad: Offers improved sanding performance and shortens time required for sanding. Reduces dust from the sanding process entering the atmosphere. Exceptionally long service life owing to continuous dust extraction.
DustPad: For use under PerforatedPad. Dust passes through the permeable material of the DustPad and is collected in the dust accumulator. The sanding disc will not clog up, thus guaranteeing an absolutely optimal sanding performance.

Item No.
LO-FI-137 PerforatedPad 100 grit
LO-FI-131 PerforatedPad 120 grit
LO-FI-136 PerforatedPad 180 grit
LO-FI-138 DustPad ø 16 inches



1



Wiping cloth
Ideally suited to wipe up excess material after oil application. Highly absorbent cloth with long lifetime. The product can also be used for cleaning tools and machines.
Material:
30 % cotton, 25 % viscose, 20 % polypropylene, 15 % polyester and 10 % other fibres.

Item No.
LO-MA-013 50x60 cm, 10 pcs.



1



1. Domestic Wood Species

Wood Species	WS EasyPrime	HS 2K Intensive ^{A.T.} transparent
Acacia / Yellow Locust	◇	◇
Acacia / Yellow Locust steamed	◇	◇
Alder	+	+
Ash	+	+
Beech natural	+	+
Beech steamed	+	◇
Birch	+	+
Black cherry	+	+
Cherry (European)	+	+
Chestnut tree	+	◇
Elm	+	+
Larch	+	+
Maple (Canadian)	+	+
Maple (European)	+	+
Oak	+	+
Olive tree	◇	◇
Pear tree	–	◇
Pine	+	+
Smoked oak	◇	◇
Spruce	+	+
Walnut (European)	+	+

2. Exotic Wood Species

Wood Species	WS EasyPrime	HS 2K Intensive ^{A.T.} transparent
Afromosia / Kokrodua	+	+
Arrurra Vermelho	–	–
Bamboo	+	–
Basralocus wood	+	+
Cabreuva	+	+
Camwood	+	◇
Coconut	+	–
Coigue	+	+
Cumaru / Almendrillo	+	+
Curupau	+	+
Curupay	+	+
Cypress	+	+
Doussie / Afzelia	+	+
Ebony	+	◇
Eucalyptus / Jarrah	+	–
Eucalyptus / Spottet Gum	+	–
Guatambu	+	+
Hard Pine (new floors)	+	+
Incienso Colorado	+	+
Ipe / Lapacho / Guaycan	◇	◇
Iroko / Kambala	–	–
Iron Wood	+	◇
Jatoba / Brazilian Cherry	+	+
Kempas	◇	+
Kotibe / Mahogany	+	+
Mahogany	+	+
Massaranduba	+	+
Mecrusse	+	+
Moluccan Ironwood	+	◇
Muhuhu	–	–
Mutenye	+	+
Opepe	+	–
Partridge Wood	+	◇
Piguia Marfin	–	–
Pitch Pine (old floors)	+	+
Purpleheart	– ¹	– ¹
Rosewood	+	◇
Rubberwood	+	◇
Sucupira	+	+
Tasmanien Oak	+	+
Tauari	+	+
Teak	+	+
Tigerwood	+	+
Wenge	+	+
Yvyraro	+	+

3. Other surfaces apart from wood

Chipboard	+	–
Multiplex	+	–
OSB Board	+	–

+ = Without limitation applicable
◇ = Application can cause problems. Consult LOBA prior to use.
– = Use is not recommended

¹ = No adhesion

1. Domestic Wood Species

Wood Species	HS 2K ImpactOil
Acacia / Yellow Locust	+
Acacia / Yellow Locust steamed	+
Alder	+
Ash	+
Beech natural	+
Beech steamed	+
Birch	+
Black cherry	+
Cherry (European)	+
Chestnut tree	+
Elm	+
Larch	+
Maple (Canadian)	+
Maple (European)	+
Oak	+
Olive tree	+
Pear tree	◇
Pine	+
Smoked oak	+
Spruce	+
Walnut (European)	+

2. Exotic Wood Species

Wood Species	HS 2K ImpactOil
Afromosia / Kokrodua	+
Arrurra Vermelho	+
Cabreuva	+
Camwood	+
Coconut	+
Cumaru / Almendrillo	+
Cypress	◇
Doussie / Afzelia	+
Eucalyptus / Jarrah	+
Eucalyptus / Spottet Gum	+
Guatambu	+
Hard Pine (new floors)	+
Ipe / Lapacho / Guaycan	◇
Iroko / Kambala	+
Iron Wood	+
Jatoba / Brazilian Cherry	+
Kotibe / Mahogany	+
Mahogany	+
Mahogany Acajou	+
Massaranduba	+
Mecrusse	+
Moluccan Ironwood	+
Muhuhu	+
Opepe	+
Partridge Wood	+
Piguia Marfin	+
Pitch Pine (old floors)	+
Purpleheart	+
Rubberwood	+
Sucupira	+
Tasmanien Oak	+
Teak	+
Wenge	+

3. Other surfaces apart from wood

Chipboard	◇
Multiplex	+
OSB Board	◇

+ = Without limitation applicable
◇ = Application can cause problems. Consult LOBA prior to use.



Loba-Wakol LLC

521C Eagleton Downs Dr | Pineville, NC 28134 | United States | Phone: +1 800 230 6456
or +1 704 527 5919 | Fax: +1 704 527 5922 | E-Mail: info@loba-wakol.com | www.loba-wakol.com | www.loba-usa.com