

# SIMPLY EXCELLENT

LAMINATE FLOORING

**ALWAYS PREMIUM.** 

# THAT'S FLOORING

# **CONTENTS**

Product advantages	06
Application areas	08
Product composition	10
Formats	14
Surfaces	15
Collections	
wineo 300	16
wineo 500	22
wineo 550	36
wineo Rock'n'Go	42
PERFECT FIT Accessories	48
Service	50
Awards & Quality	52
Floor Viewer	54
Collection overview	55
Symbols	57





Carefully selected collections, sustainably produced and perfectly aligned – wineo laminate flooring makes all the difference. Every day, again and again and in every area with quality, performance and design.

#### **CREATIVE DESIGNS**

Individual top seller decors, the right design for every taste.

#### **STRONG PROPERTIES**

Hard-wearing, water-resistant and easy to lay – versatile in use.

#### **SUPERIOR QUALITY**

High-quality and durable – we give up to 25 years guarantee.

#### **GERMAN PRODUCTION**

Developed and produced in Ostwestfalen-Lippe. 100 % Made in Germany.





#### **DURABLE**

wineo laminate flooring is non-staining. Even furniture or chair castors leave no traces.



#### SUITABLE FOR UNDERFLOOR HEATING

In combination with suitable underlay material, the laminate flooring can be laid on underfloor heating without any problems.



#### **MOISTURE-RESISTANT**

The Aqua-Stop profile sealing protects the laminate flooring against liquids and moisture. Non-perceptible swelling - up to four times less than conventional laminate flooring.



#### **SUITABLE FOR DAMP AREAS**

Thanks to the low-swelling HDF carrier board with an edge sealing, the laminate flooring are optimally protected against moisture.



#### **EASY CARE**

Thanks to the melamine resin overlay, the laminate flooring is easy to clean.



#### **UV-RESISTANT**

Even when exposed to sunlight, the laminate flooring does not change thanks to its high UV-resistance.



#### **ANTISTATIC**

The static charge of the surface, for example in dry room air, is reduced and dust does not adhere.

# **APPLICATION AREAS**

wineo laminate flooring can be used in almost all areas. The demands on the sub floor are low, so that the panels can be installed on almost any base – even if it has small irregularities. Just as easy as it is to lay, the laminate flooring can be taken up and reused.



wineo laminate flooring is suitable for damp areas.












## PRODUCT COMPOSITION

#### wineo 300 | wineo 500





- 1 Surface texture

  Various surface embossing ensures highest level of authenticity.
- Wear layer
  The hard-wearing melamine resin overlay
  is the basis for the classification into the
  corresponding application areas.
- 3 **Decor**The decor paper offers a wide range of design options.
- 4 Core board
  The highly compressed HDF core board is swell-protected.
- 5 Profile connection
  Thanks to the tried-and-tested LocTec®
  locking system, the panels can easily be
  clicked into each other. wineo 500 also
  features a locking on the short panel side.

- 6 Aqua-Stop profile sealing


  The Aqua-Stop profile sealing protects the entire connection system from moisture.
- 7 Backing
  The melamine resin backing serves
  for balance and guarantees high
  dimensional stability.
  - Integrated: wineo 300 is optionally available with an integrated noiseREDUCT underlay.\*

    As accessory: The PU underlay soundSTOP (only wineo 500) or soundPROTECT are available separately for all products.

    For using these we grant +5 years on all standard guarantees.

f






- Surface texture Different surfaces provide for matt and high-gloss optics.
- 2 Wear layer The top coat is the basis for the classification into the corresponding application areas.
- Decor The decor paper offers a wide range of design options.
- **Core board** The highly compressed HDF core board is swell-protected.
- **Profile connection** Thanks to the tried-and-tested LocTec® locking system, the panels can easily be clicked into each other.

- **Backing** The kraft paper backing serves for balance and guarantees high dimensional stability.
- Underlay As accessory: The PU underlay soundPROTECT is available separately for all products. For using these we grant +5 years on all standard guarantees.

#### wineo Rock'n'Go





- Surface texture Different surface embossings provide an extremely high level of authenticity.
- Wear layer The particularly hard-wearing melamine resin overlay is the basis for classification in the corresponding application areas.
- Decor The decor paper offers a wide range of design possibilities.
- Core board The highly compressed HDF core board is swell-protected.
- **Profile connection** The Fold-Down locking system makes the product very easy and quick to lay.

- Aqua-Stop profile sealing The innovative profile sealing protects the entire connection system from moisture and is therefore quite moisture-resistant.
- **Backing** The melamine resin backing serves the balance and guarantees a high dimensional stability.
  - Sound stop layer All products have an integrated underlay soundSTOP including protective film. By peeling off the protective film, it is fixed to the sub floor and the walking and impact sound is reduced many times over (50 % more quiet than conventional laminate).



#### **AQUA-STOP TECHNOLOGY**

Thanks to Aqua-Stop technology, wineo laminate flooring remains resistant against liquids and moisture. This all round edge sealing protects the entire connection system and, in combination with high-quality carrier boards, is suitable for use in damp rooms such as kitchens, bathrooms or wellness zones. wineo laminate floorings equipped with Aqua-Stop show no visible signs of swelling, up to four times less compared to conventional laminate products.



#### SOUND-STOP TECHNOLOGY

The adhesive fixing of the soundSTOP underlay directly to the subfloor is state of the art and makes the floor 50 % more quiet than conventional laminate. With wineo Rock'n'Go, the soundSTOP underlay is pre fitted. The soundSTOP underlay is also available seperately, in order to turn every other laminate flooring with Fold-Down locking quiet.



#### **INSTALL READY**

Thanks to an integrated underlay, products marked with install ready can be laid directly onto a prepared subfloor.

# **FORMATS**

#### wineo 300



## wineo 500



# wineo 550



## wineo Rock'n'Go



# **SURFACES**

Matt surface

The wineo laminate flooring have different surfaces that are individually matched to the decors. Embossed wood texture ensure that your flooring feels genuine. You will find a note to the respective surface under the decorative illustrations on the collection pages.



High gloss surface





# SIMPLY BASIC. ALWAYS PREMIUM.

The optimal entry into the laminate world – wineo 300 has proven to be excellent with a harmonious panel format, an attractive price-performance ratio, excellent quality and outstanding product properties. Thanks to the innovative Aqua-Stop technology, the laminate flooring is optimally protected against moisture.

Optionally, the wineo 300 is also available with an integrated noiseREDUCT underlay, which means that the product is immediately ready for installation and the impact and walking noise is optimally reduced.

Format: M

 $1288 \times 195 \, \text{mm}$ 

 $\begin{tabular}{ll} \textbf{Product thickness:} & 7\,mm \mid 9\,mm \ \mbox{(with integrated underlay noiseREDUCT*)} \end{tabular}$ 

 $\textbf{Panels/Box:} \hspace{1.5cm} 10/2.51m^2 \mid 8/2.01m^2 \hspace{0.1cm} \text{(with integrated underlay noiseREDUCT*)}$ 





















**Canadian Maple**3-Strip | Fine wooden pore

LA001N | LA001NC\*



Classic Beech 3-Strip | Fine wooden pore





Classic Oak
3-Strip | Fine wooden pore



Natural Walnut 3-Strip | Fine wooden pore

LA012N | LA012NC\*





1-Strip | Rustic matt wood structure



Moon Oak
1-Strip | Rustic matt wood structure



Traditional Oak Brown
1-Strip | Rustic matt wood structure



London Oak
1-Strip | Rustic matt wood structure



Welsh Pale Oak 1-Strip | Rough saw surface







1-Strip | Rustic matt wood structure



Welsh Dark Oak

1-Strip | Rough saw surface







# SIMPLY OAK. ALWAYS PREMIUM.

Modern and yet timelessly beautiful – wineo 500 is quite impressive featuring 25 perfectly coordinated oak decors in best quality, five characteristics from calm to rustic and different colours from light to dark. With three formats, an attractive V4 joint and practical Aqua-Stop, it is the highlight in any room. In addition, the wineo 500 is suitable up to utility class 33 due to its particularly resistant surface.

A perfectly thought-out advisory system of design, quality and performance.

M | 1290 × 195 mm

L | 1522 × 246 mm

XXL | 1847 × 246 mm

# FOREVER

THE WAY TO FIND JUST THE RIGHT FLOOR!



# **UNIQUE DECOR SYSTEM**

#### **5 OAK CHARACTERS IN 5 COLOURS**



# wineo 500 smooth oak

XXL Format: Μ

> 1290 × 195 mm 1522 × 246 mm 1847 × 246 mm

**Product thickness:** 8mm 8mm 8mm Panels / Box: 9/2.26 m<sup>2</sup> 8/3.00 m<sup>2</sup> 6/2.73 m<sup>2</sup>





















Smooth Oak White 1-Strip | Silk matt surface

M: LA164MV4 L: LA164LV4 XXL: LA164XXLV4



Smooth Oak Beige 1-Strip | Silk matt surface

M: LA165MV4 L: LA165LV4 XXL: LA165XXLV4



1-Strip | Silk matt surface L: LA166LV4 XXL: LA166XXLV4



Smooth Oak Darkbrown 1-Strip | Silk matt surface





Smooth Oak Grey 1-Strip | Silk matt surface

M: LA168MV4 L: LA168LV4 XXL: LA168XXLV4



# wineo 500 flowered oak

XXL Format: Μ

> 1290 × 195 mm 1522 × 246 mm 1847 × 246 mm

**Product thickness:** 8mm 8mm Panels / Box: 9/2.26 m<sup>2</sup> 8/3.00 m<sup>2</sup> 6/2.73 m<sup>2</sup>
























Flowered Oak White 1-Strip | Silk matt surface

M: LA169MV4 L: LA169LV4 XXL: LA169XXLV4



Flowered Oak Beige 1-Strip | Silk matt surface

M: LA170MV4 **L**: LA170LV4 XXL: LA170XXLV4



Flowered Oak Brown 1-Strip | Silk matt surface

M: LA171MV4 **L**: LA171LV4 XXL: LA171XXLV4



Flowered Oak Darkbrown 1-Strip | Silk matt surface

M: LA172MV4 L: LA172LV4 XXL: LA172XXLV4



Flowered Oak Grey 1-Strip | Silk matt surface

M: LA173MV4 L: LA173LV4 XXL: LA173XXLV4



# wineo 500 balanced oak

XXL Format: Μ

> 1290 × 195 mm 1522 × 246 mm 1847 × 246 mm

**Product thickness:** 8mm 8mm Panels / Box: 9/2.26 m<sup>2</sup> 8/3.00 m<sup>2</sup> 6/2.73 m<sup>2</sup>





















**Balanced Oak White** 1-Strip | Brushed matt structure

M: LA179MV4 L: LA179LV4 XXL: LA179XXLV4



Balanced Oak Beige 1-Strip | Brushed matt structure

M: LA180MV4 L: LA180LV4 XXL: LA180XXLV4



1-Strip | Brushed matt structure

M: LA181MV4 L: LA181LV4 XXL: LA181XXLV4



Balanced Oak Darkbrown 1-Strip | Brushed matt structure

M: LA182MV4 L: LA182LV4 XXL: LA182XXLV4



Balanced Oak Grey 1-Strip | Brushed matt structure

M: LA183MV4 L: LA183LV4 XXL: LA183XXLV4



# wineo 500 wild oak

Format: M L XXL

 $1290 \times 195 \, \text{mm}$   $1522 \times 246 \, \text{mm}$   $1847 \times 246 \, \text{mm}$ 

 Product thickness:
 8 mm
 8 mm
 8 mm

 Panels/Box:
 9/2.26 m²
 8/3.00 m²
 6/2.73 m²





















Wild Oak White 1-Strip | Brushed matt structure





Wild Oak Beige 1-Strip | Brushed matt structure

**M**: LA185MV4 **L**: LA185LV4 **XXL**: LA185XXLV4



Wild Oak Brown 1-Strip | Brushed matt structure

**M**: LA186MV4 **L**: LA186LV4 **XXL**: LA186XXLV4



Wild Oak Darkbrown 1-Strip | Brushed matt structure

**M**: LA187MV4 **L**: LA187LV4 **XXL**: LA187XXLV4



Wild Oak Grey 1-Strip | Brushed matt structure

**M**: LA188MV4 **L**: LA188LV4 **XXL**: LA188XXLV4



# wineo 500 strong oak

Format: M L XXL

 $1290 \times 195 \, \text{mm}$   $1522 \times 246 \, \text{mm}$   $1847 \times 246 \, \text{mm}$ 

 Product thickness:
 8 mm
 8 mm
 8 mm

 Panels/Box:
 9/2.26 m²
 8/3.00 m²
 6/2.73 m²





















Strong Oak White 1-Strip | Brushed matt structure

**M**: LA174MV4 **L**: LA174LV4 **XXL**: LA174XXLV4



Strong Oak Beige 1-Strip | Brushed matt structure

**M**: LA175MV4 **L**: LA175LV4 **XXL**: LA175XXLV4



Strong Oak Brown 1-Strip | Brushed matt structure

**M**: LA176MV4 **L**: LA176LV4 **XXL**: LA176XXLV4



Strong Oak Darkbrown
1-Strip | Brushed matt structure

**M**: LA177MV4 **L**: LA177LV4 **XXL**: LA177XXLV4



Strong Oak Grey 1-Strip | Brushed matt structure

**M**: LA178MV4 **L**: LA178LV4 **XXL**: LA178XXLV4





# LAMINATE

### wineo 550

# SIMPLY STYLISH. ALWAYS PREMIUM.

Modern matt or elegant high gloss – the wineo 550 has proven to be excellent with its 8 mm construction height and stylish plain decors in impressive tile format. The collection is the ideal partner for unique spatial experiences at home, in shop fitting or at trade fairs.

## wineo 550 matt

Format: tile

853 × 331 mm

**Product thickness:** 8 mm **Tiles/Box:** 8/2.26 m<sup>2</sup>
















Black LA067CM-01 Matt surface



White LA068CM-01 Matt surface



Umbra LA069CM-01 Matt surface



Traffic LA072CM-01 Matt surface



## wineo 550 high gloss

Format: tile

853 × 331 mm

**Product thickness:** 8mm

Tiles/Box: 8/2.26 m<sup>2</sup>


















LA067CH-01



LA068CH-01



Umbra LA069CH-01



Traffic LA072CH-01

High gloss surface

High gloss surface

High gloss surface







## wineo Rock'n'Go SIMPLY ROCKABLE.

**ALWAYS PREMIUM.** 

Even more practical, even more versatile the laminate flooring with system combines everything you need. The laminate flooring has a particularly high-quality finish and is pleasantly quiet - thanks to the integrated soundSTOP underlay and maintains maximum moisture resistance thanks to it's Agua-Stop technology. All this in 12 rockable decors with individual wood designs, such as the distinctive OSB decors. It rocks every room!



Format: M

1288 × 195 mm

**Product thickness:** 9 mm (with integrated underlay soundSTOP)

**Panels / Box:** 8/2.01 m<sup>2</sup>
























Born to be Wild LA151SYS
OSB structure



Under Pressure LA152SYS
0SB structure



Paint it Black LA153SYS OSB structure



Knocking on heavens door Rustic matt wood structure





Dancing in the Dark
Rustic matt wood structure

LA149SYSV4







House of the rising sun Rough matt wood structure

LA143SYSV4



**Hotel California** Rustic matt wood structure



Here comes the sun Rustic matt wood structure

LA145SYSV4



**London Calling** Rustic matt wood structure



Rough matt wood structure

LA146SYSV4



Man on the Moon Rustic matt wood structure

LA142SYSV4



I was made for loving you Rustic matt wood structure

LA147SYSV4



## PERFECT FIT ACCESSORIES

#### **PU UNDERLAY**

We recommend our underlay soundSTOP, soundPROTECT and soundPROTECT PROFI for wineo laminate flooring. The basis is *ecuran*, a high-performance composite material which is predominantly made from vegetable oils such as canola or castor oil and naturally occurring mineral components such as chalk.

- fast, energy-efficient distribution of ground heat
- outstanding noise reduction
- long-life performance of at least 30 years
- resilience almost 100 %
- sustainable raw materials
- **■** without chlorine, plasticizers and solvents
- the best combination of walking and impact sound reduction
- super quiet and efficient, for a stable click connection

#### soundSTOP

soundPROTECT



#### soundPROTECT SD

integrated
VAPOUR
BARRIER



#### soundPROTECT PROFI SD

Art. no. UPU200SD

Fits perfectly for: wineo 300 | 500 | 550

Impact sound reduction ~ 19 dB

Reflected walking sound ~ 28 %



## **f**

Detailed information can be found in our accessories brochure:

Product no. 20091021

Download now:











If a wineo PERFECT FIT
PU underlay (soundPROTECT,
soundSTOP) is used in
combination with a suitable
wineo flooring product, the
wineo guarantee will be
extended by 5 years.





Fits perfectly for: wineo 300 | 500 | 550 | Impact sound reduction  $\sim 20\, dB$  Reflected walking sound  $\sim 31\,\%$  Art. no. UPU100

#### **PE UNDERLAY**

The reliable protection for noise reduction.

- quiet and light weight
- **■** for use with underfloor heating

#### noisePROTECT




Fits perfectly for: wineo 300 | 550 Impact sound reduction ~ 19 dB Reflected walking sound ~ 20 % Art. no. UPE100

#### **XPS UNDERLAY**

The simple underlay for noise reduction.

- quiet and light weight
- for use as heat insulation

#### noiseREDUCT




Fits perfectly for: wineo 300 | 550 Impact sound reduction ~ 20 dB Reflected walking sound ~ 14 % Art. no. UXPS100

#### **WOOD FIBER BOARD**

The strong insulation board for the professional.

■ floor leveling, heat insulating, durable

#### insulationBOARD



Fits perfectly for: wineo 300 | 500 | 550 Impact sound reduction ~ 22 dB Reflected walking sound ~ 11 % Art. no. UHF100

#### noisePROTECT SD



Fits perfectly for: wineo 300 | 550 Impact sound reduction ~ 19 dB Reflected walking sound ~ 15 % Art. no. UPE100SD

#### noiseREDUCT SD



Fits perfectly for: wineo 300 | 550 Impact sound reduction ~ 20 dB Reflected walking sound ~ 14 % Art. no. UXPS100 SD



#### **SKIRTING BOARDS**

- decor matching MDF skirtings for all wineo floor coverings
- universally usable skirtings MDF as well as plastic/aluminium
- installation heights from 60 mm to 100 mm
- plastic mounting clips included in the range of accessories; alternatively glue or tack
- self-adhesive corner elements for easy installation



#### **PROFILES**

- Comfort Profiles (self-adhesive profiles) for do-it-yourselfers
- Premium Profiles (screwable profiles) for professionals
- profile types for various applications: transition, adjustment and end profiles, angle profiles and stair nosing profiles

## **SERVICE**

We are partners for trade, architects, property developers and everyone who appreciates good flooring. As a result, we offer an extensive range of services. And, to stay fully up to date, you can just visit us on YouTube, Facebook, Twitter or Pinterest.



#### **TECHNICAL SUPPORT**

Do you have any questions about our products, their areas-of application or their installation?

Our capable technical-team is happy to help you:

Tel.: +49 (0) 52 37 609 - 530



#### **MARKETING SUPPORT**

We support you with a wide range of samples and printed materials for product presentation and sales promotion at the POS. You can find an overview of all our presentation media, from brochures to displays, in our sales promotion brochure, "Advertising with wineo".

Naturally, we can also work with you to tailor materials to your **specific needs**.

Just get in touch!




#### **SEMINARS**

Take advantage of our seminar offer to improve your know-how, optimize your installation technique or sales strategy and reap the benefits of a successful partnership. wineo product training seminars are informative, practical and tailored, and prepare you fully for working with our floors. You can find more information on our website, including how to register for a seminar.



#### **NEWSLETTER**

Stay in touch with us: it's easy to sign up for the wineo newsletter on our website. This will guarantee that you don't miss out on anything and will always be kept up to date.



#### **EN.WINEO.DE**

- information and references as well as relevant downloads on the products
- retailer portal with direct ordering option and query of product availability
- product search by characteristic, colour, format, installation height and utilisation class
- find a retailer
- video portal with plenty of tips and tricks, such as installation instructions





THE BEST QUALITY
FOR OVER 70 YEARS

For us, outstanding quality means more than an excellent product. As a family business in its 3rd generation we carry a high level of social and ecological responsibility. That's why we always provide you with the greatest possible level of transparency. And therefore even more safety.

- many quality controls from the initial mixing of the ingredients to the completion stage
- traceability of the exact time of production via a reverse-side overprint
- outstanding attributes regarding durability, maintenance and safety





(applies to wineo 550)

#### **CE** mark of conformity

The CE mark confirms that the product has been tested and meets all the EU-wide requirements for safety, health protection and environmental protection.



#### A+

Just like the "Blue Angel" in Germany, the A+ seal identifies our products as ecological, healthy and user friendly in the French market.



www.blauer-engel.de/uz176

#### "Blue Angel" (Blauer Engel)

The "Blue Angel" guarantees that our products and services fulfill high requirements placed on environmental, health and usage properties. Criteria must be met for each product group, which are checked every three to four years by the Federal Environment Agency.




#### **PEFC**

The PEFC quality seal is based on very strict guidelines for managing our forests in a sustainable manner and guarantees that timber is used from verified cultivation sources. The whole product manufacturing process - from the raw material through to the ready-to-use end product - is certified and verified by independent assessors.

## **FLOOR VIEWER**

The all new wineo floor viewer enables anyone to simulate wineo floorings quick and easy within their own four walls, thus providing an outstanding impression of the desired floor.

#### floorviewer.wineo.de



## **COLLECTION OVERVIEW**

Collection	wineo 300	wineo 500 M	wineo 500 L
Installation Type	Click	Click	Click
Locking system	LocTec®	Fold-Down	Fold-Down
Core board		Highly compre	essed carrier board top profile sealing
Format	1288 x 195 mm	1290 x 195 mm	1522 x 246 mm
Product thickness with integrated underlay	7 mm 9 mm	8 mm -	8 mm -
Panels/Box with integrated underlay	10 / 2.51 m² 8 / 2.01 m²	9/2.26 m <sup>2</sup>	8 / 3.00 m <sup>2</sup>
Boxes/Pallet with integrated underlay	52 / 130.52 m² 52 / 104.52 m²	52 / 117.52 m² -	44 / 132.00 m <sup>2</sup>
Authentic joint design	-	V4 joint	V4 joint
available with integrated underlay	noiseREDUCT	-	-
Utilization class   EN ISO 10874	23/31	23/33	23/33
Abrasion resistance EN 13329, Appendix E	AC3	AC5	AC5
Impact resistance EN 13329, Appendix H	Small ball $\geq$ 8 N Large ball $\geq$ 500 mm	Small ball $\geq$ 15 N Large ball $\geq$ 1000 mm	Small ball $\geq$ 15 N Large ball $\geq$ 1000 mm
Reaction to fire   EN 13501-1	$C_{fi} - s1$	$C_{ff} - s1$	$C_{fi} - s1$
Slip resistance   EN 13893	$\mu \geq 0.30 - DS$	$\mu \geq 0.30 - DS$	$\mu \geq 0.30 - DS$
Anti-static properties   EN 1815	≤ 2 kV	≤ 2 kV	≤ 2 kV
Resistance to staining   EN 438			
Light fastness   EN ISO 105-B02 (procedure 2)			
Impression after constant load   EN ISO 24343-1			
Effect of a furniture leg   EN 424			
Castor chair test   EN 425			
Suitable for underfloor heating	In comb	ination with suitable underlay material s	uch as soundPROTECT or equivale
Thermal resistance in $(m^2K)/W\mid$ EN 12667 with integrated underlay	0.053 0.112	0.060	0.060
Impact sound reduction   ISO 717-2 Reflected walking sound with integrated underlay	~ 19 dB 13 %	-	-
Formaldehyde emission   EN 717-1			
Swelling value after 24 hrs. (Windmöller factory mesurement)	≤ 5 %	≤ 5 %	≤ 5 %
Gurantee for private use according to Windmoeller guarantee conditions	15 years	25 years	25 years
Guarantee extension when installed on PU Underlays	+5 years	+5 years	+5 years
Decors	12	25	25
Side	16 – 21	22 – 35	22 – 35

<sup>\* =</sup> Abraison resistance, Appendix A

<sup>\*2 =</sup> LA149SYSV4/Dancing in the Dark = AC4/UC 23/32

wineo 500 XXL	wineo 550 matt	wineo 550 high gloss	wineo Rock'n'Go
Click	Click	Click	Click
Fold-Down	LocTec®	LocTec®	Fold-Down
	Highly	compressed carrier board	Highly compressed carrier board with Aqua-Stop profile sealing
1847 x 246 mm	853 x 331 mm	853 x 331 mm	1288 x 195 mm
8 mm	8 mm -	8 mm	- 9 mm
6 / 2.73 m <sup>2</sup>	8 / 2.26 m <sup>2</sup>	8 / 2.26 m <sup>2</sup>	-
-	-	-	8/2.01 m <sup>2</sup>
44 / 120.12 m² -	45 / 101.70 m² -	45 / 101.70 m² -	- 48 / 96.48 m²
V4 joint	_		V4 joint
			(for selected decors)
-	-	-	soundSTOP
23/33	23/32	23/32	23/33*2
AC5	AC4	AC4*	AC5*2
Small ball ≥ 15 N Large ball ≥ 1000 mm	Small ball ≥ 12 N Large ball ≥ 750 mm	Small ball $\geq$ 12 N Large ball $\geq$ 750 mm	Small ball ≥ 15 N Large ball ≥ 1000 mm
$C_{fi} - s1$	$B_{fi} - s1$	$B_{ff} - s1$	$C_{\rm fl} - s1$
$\mu \geq 0.30 - DS$	$\mu \geq 0.30 - \text{DS}$	$\mu \geq 0.30 - DS$	$\mu \geq 0.30 - DS$
≤ 2 kV	-	-	≤ 2 kV
Group 1+2: Grade 5/Group	3: Grade 4		
≥ 6			
Residual impression ≤ 0			
Foot type 0 – no visible o	change		
000 revolutions – no damage with	•		
	ater underfloor heating systems and regul		emperature of 27 °C.
0.060	0.060	0.060	- 0.060
-	-	-	17 dB 50 %
E1			
≤ 5 %	-	-	≤ 5 %
25 years	20 years	20 years	30 years
+5 years	+5 years	+5 years	already integrated
			40
25	4	4	12

## **SYMBOLS**

#### **PRODUCT FEATURES**



LocTec® locking



Fold-Down locking



Install Ready



Authentic joint design (V4)



Swell-resistant HDF core board with new Aqua-Stop edge sealing for maximum moisture resistance





Underlay noiseREDUCT





Underlay soundSTOP

#### **UTILIZATION CLASSES**



Utilization class 23: Domestic area with intensive usage



Utilization class 31: Commercial sector with low or occasional usage



Utilization class 32: Commercial sector with average usage



Utilization class 33: Commercial sector with heavy usage





Abrasion resistance: AC3 (corresponds to utilization class 23/31)





Abrasion resistance: AC4 (corresponds to utilization class 23/32)





Abrasion resistance: AC5 (corresponds to utilization class 23/33)

#### **GUARANTEE**





15 years guarantee (for private use)





20 years guarantee (for private use)





25 years guarantee (for private use)





30 years guarantee (for private use)

Windmöller GmbH

Nord-West-Ring 21 D-32832 Augustdorf

Tel.: +49 (0) 52 37 609 - 0 Fax: +49 (0) 52 37 609 - 309

info@wineo.de

www.wineo.de

Presented by:

Wineo